ORDER REFERENCE EXAMPLE

095	U2	B	30	1	V	A	CD	A	100	190

Frame Size:
055
075
095
115
142
190

Motor Type:
E2 = 220V
U2 = 480V

Stator Length:
A, B, C, D*,
E*, F*, G*, H*

Rated Speed:
10 = 1000 rpm
20 = 2000 rpm
25 = 2500 rpm
30 = 3000 rpm
40 = 4000 rpm
45 = 4500 rpm
50 = 5000 rpm
60 = 6000 rpm

Brake:
0 = Not fitted
1 = Parking brake fitted 24VDC
X = Special

Connection Type:
A = Power and Signal 90° fixed
B = Power and Signal 90° rotatable
C = Power 90° Signal vertical
V = Power and Signal Vertical
X = Special

Output Shaft:
A = Key
B = Without key
X = Special

Feedback Device:
AE = Resolver
AR = Resolver size 15**
CD = Encoder 4096
CP = Encoder 4096**
MD = Encoder 2048
MP = Encoder 2048**
PD = Sin/Cos SPLM
RA = Sin/Cos Multi turn SRM50
SA = Sin/Cos Single turn SRS50
TL = Sin/Cos Multi turn SKM36**
UL = Sin/Cos Single turn SKS36**
XX = Special

Inertia:
A = Standard inertia
B = High inertia

PCD*:**
New Feature

055 Frame only
063 Std
070 Opt
075 Frame only
075 Std
080 Opt
085 Opt
095 Frame only
100 Std
098 Opt
115 Opt
115 Frame only
115 Std
130 Opt
145 Opt
142 Frame only
165 Std
149 Opt
190 Frame only
215 Std

Shaft Diameter*:**
New Feature

055 Frame only
09.0 Opt
11.0 A-C
075 Frame only
11.0 A
14.0 B-D
19.0 Maximum
095 Frame only
14.0 A
19.0 B-E
22.0 Maximum
115 Frame only
19.0 A-C
24.0 D-E
33.0 Maximum
142 Frame only
24.0 A-E
33.0 Maximum
190 Frame only
32.0 A-H
42.0 Maximum

* Not available on some frame sizes
** Available on the 55 frame motor only
*** NEMA dimensions available on request